

Motori NEMA trifase autofrenanti
NEMA three-phase induction self brake motors
Moteurs NEMA asynchrones triphasés autofrénants
Drehstrombremsmotoren NEMA

Potenza / Power		rpm		Poli Poles	IEC frame	NEMA C FACE Mounting	In [A]	Rend.		Cn [Nm]		Cn [lb·in]		J- [kgm²]	J- [lb.ft²]	Coppia Frenante Brake Torque		WGT		C Dimension	
hp	kW							50Hz	60Hz	50Hz	60Hz	50Hz	60Hz			50Hz	60Hz	[Nm]	[lb·in]	[Kg]	[lb]
230V/400V/50Hz - 208V 230V/460/60Hz	230V/400V/50Hz - 208V 230V/460/60Hz	50Hz	60Hz			400V/50Hz 460V/60Hz															
1/4	0,18	2950	3540	2	IEC80	56C	0,53	65	67	0,58	0,49	5,16	4,30	0,0008	0,0190	5	44,29	10,2	22,49	313,0	12,32
1/4	0,18	1460	1752	4	IEC80	56C	0,58	60	62	1,18	0,98	10,43	8,69	0,0014	0,0332	5	44,29	10,2	22,49	313,0	12,32
1/4	0,18	970	1164	6	IEC80	56C	0,62	56	58	1,77	1,48	15,70	13,09	0,0020	0,0475	5	44,29	10,4	22,93	313,0	12,32
1/4	0,18	720	864	8	IEC80	56C	0,63	55	57	2,39	1,99	21,16	17,63	0,0020	0,0475	5	44,29	10,5	23,15	313,0	12,32
1/4	0,18	480	576	12	IEC80	56C	0,83	42	43	3,58	2,99	31,73	26,45	0,0030	0,0712	5	44,29	12,7	28,00	313,0	12,32
1/3	0,25	2940	3528	2	IEC80	56C	0,70	69	71	0,81	0,68	7,20	6,00	0,0008	0,0190	5	44,29	10,2	22,49	313,0	12,32
1/3	0,25	1450	1740	4	IEC80	56C	0,74	65	67	1,65	1,37	14,59	12,16	0,0014	0,0332	5	44,29	10,2	22,49	313,0	12,32
1/3	0,25	960	1152	6	IEC80	56C	0,83	58	60	2,49	2,07	22,04	18,36	0,0020	0,0475	5	44,29	10,4	22,93	313,0	12,32
1/3	0,25	710	852	8	IEC80	56C	0,85	57	59	3,36	2,80	29,80	24,83	0,0025	0,0593	5	44,29	10,5	23,15	313,0	12,32
1/3	0,25	470	564	12	IEC80	56C	1,15	42	43	5,08	4,23	45,01	37,51	0,0030	0,0712	5	44,29	12,7	28,00	313,0	12,32
1/2	0,37	2920	3504	2	IEC80	56C	1,00	71	73	1,21	1,01	10,72	8,94	0,0008	0,0190	5	44,29	10,2	22,49	313,0	12,32
1/2	0,37	1435	1722	4	IEC80	56C	1,06	67	69	2,46	2,05	21,82	18,18	0,0014	0,0332	5	44,29	10,2	22,49	313,0	12,32
1/2	0,37	955	1146	6	IEC80	56C	1,10	65	67	3,70	3,08	32,79	27,32	0,0020	0,0475	5	44,29	10,4	22,93	313,0	12,32
1/2	0,37	700	840	8	IEC80	56C	1,19	60	62	5,05	4,21	44,73	37,28	0,0030	0,0712	10	88,57	11,1	24,48	317,0	12,48
1/2	0,37	460	552	12	IEC80	56C	1,55	46	47	7,68	6,40	68,07	56,72	0,0030	0,0712	10	88,57	13,3	29,33	317,0	12,48
3/4	0,55	2900	3480	2	IEC80	56C	1,45	73	75	1,81	1,51	16,05	13,37	0,0008	0,0190	5	44,29	10,2	22,49	313,0	12,32
3/4	0,55	2900	3480	2	IEC80	143C	1,45	73	75	1,81	1,51	16,05	13,37	0,0008	0,0190	5	44,29	10,2	22,49	314,5	12,38
3/4	0,55	2900	3480	2	IEC80	145C	1,45	73	75	1,81	1,51	16,05	13,37	0,0008	0,0190	5	44,29	10,2	22,49	314,5	12,38
3/4	0,55	1420	1704	4	IEC80	56C	1,56	68	70	3,70	3,08	32,78	27,31	0,0014	0,0332	5	44,29	10,2	22,49	313,0	12,32
3/4	0,55	1420	1704	4	IEC80	143C	1,56	68	70	3,70	3,08	32,78	27,31	0,0014	0,0332	5	44,29	10,2	22,49	314,5	12,38
3/4	0,55	1420	1704	4	IEC80	145C	1,56	68	70	3,70	3,08	32,78	27,31	0,0014	0,0332	5	44,29	10,2	22,49	314,5	12,38
3/4	0,55	940	1128	6	IEC80	56C	1,56	68	70	5,59	4,66	49,51	41,26	0,0025	0,0593	10	88,57	12,8	28,22	317,0	12,48
3/4	0,55	940	1128	6	IEC80	143C	1,56	68	70	5,59	4,66	49,51	41,26	0,0025	0,0593	10	88,57	12,8	28,22	318,5	12,54
3/4	0,55	940	1128	6	IEC80	145C	1,56	68	70	5,59	4,66	49,51	41,26	0,0025	0,0593	10	88,57	12,8	28,22	318,5	12,54
1	0,75	2880	3456	2	IEC80	56C	1,90	76	78	2,49	2,07	22,04	18,36	0,0008	0,0190	5	44,29	10,2	22,49	313,0	12,32
1	0,75	2880	3456	2	IEC80	143C	1,90	76	78	2,49	2,07	22,04	18,36	0,0008	0,0190	5	44,29	10,2	22,49	314,5	12,38
1	0,75	2880	3456	2	IEC80	145C	1,90	76	78	2,49	2,07	22,04	18,36	0,0008	0,0190	5	44,29	10,2	22,49	314,5	12,38
1	0,75	1400	1680	4	IEC80	56C	2,06	70	72	5,12	4,27	45,33	37,78	0,0017	0,0403	10	88,57	12,1	26,68	317,0	12,48
1	0,75	1400	1680	4	IEC80	143C	2,06	70	72	5,12	4,27	45,33	37,78	0,0017	0,0403	10	88,57	12,1	26,68	318,5	12,54
1	0,75	1400	1680	4	IEC80	145C	2,06	70	72	5,12	4,27	45,33	37,78	0,0017	0,0403	10	88,57	12,1	26,68	318,5	12,54
1	0,75	920	1104	6	IEC80	56C	2,09	69	71	7,79	6,49	68,99	57,49	0,0026	0,0617	10	88,57	13,3	29,33	317,0	12,48
1	0,75	920	1104	6	IEC80	143C	2,09	69	71	7,79	6,49	68,99	57,49	0,0026	0,0617	10	88,57	13,3	29,33	318,5	12,54
1	0,75	920	1104	6	IEC80	145C	2,09	69	71	7,79	6,49	68,99	57,49	0,0026	0,0617	10	88,57	13,3	29,33	318,5	12,54
1 1/2	1,10	2860	3432	2	IEC80	56C	2,72	78	80	3,67	3,06	32,55	27,12	0,0010	0,0230	10	88,57	12,1	26,68	317,0	12,48
1 1/2	1,10	2860	3432	2	IEC80	143C	2,72	78	80	3,67	3,06	32,55	27,12	0,0010	0,0230	10	88,57	12,1	26,68	318,5	12,54
1 1/2	1,10	2860	3432	2	IEC80	145C	2,72	78	80	3,67	3,06	32,55	27,12	0,0010	0,0230	10	88,57	12,1	26,68	318,5	12,54
1 1/2	1,10	2900	3480	2	IEC100	182C	2,72	78	80	3,62	3,02	32,10	26,75	0,0053	0,1258	16	141,72	23,5	51,82	427,0	16,81
1 1/2	1,10	2900	3480	2	IEC100	184C	2,72	78	80	3,62	3,02	32,10	26,75	0,0053	0,1258	16	141,72	23,5	51,82	427,0	16,81
1 1/2	1,10	1390	1668	4	IEC80	56C	2,99	71	73	7,56	6,30	66,97	55,81	0,0023	0,0546	10	88,57	13,3	29,33	317,0	12,48
1 1/2	1,10	1390	1668	4	IEC80	143C	2,99	71	73	7,56	6,30	66,97	55,81	0,0023	0,0546	10	88,57	13,3	29,33	318,5	12,54
1 1/2	1,10	1390	1668	4	IEC80	145C	2,99	71	73	7,56	6,30	66,97	55,81	0,0023	0,0546	10	88,57	13,3	29,33	318,5	12,54
1 1/2	1,10	1440	1728	4	IEC100	182C	2,99	71	73	7,30	6,08	64,64	53,87	0,0075	0,1780	16	141,72	24,0	52,92	427,0	16,81
1 1/2	1,10	1440	1728	4	IEC100	184C	2,99	71	73	7,30	6,08	64,64	53,87	0,0075	0,1780	16	141,72	24,0	52,92	427,0	16,81



Potenza / Power		rpm		Poli Poles	IEC frame	NEMA C FACE Mounting	In [A] 400V/50Hz 460V/60Hz	Rend.		Cn [Nm]		Cn [lb·in]		J- [kgm²]	J- [lb.ft²]	Coppia Frenante Brake Torque		WGT		C Dimension	
hp	kW							50Hz	60Hz	50Hz	60Hz	50Hz	60Hz			50Hz	60Hz	[Nm]	[lb-in]	[Kg]	[lb]
1 1/2	1,10	960	1152	6	IEC100	182C	2,86	74	76	10,95	9,12	96,97	80,80	0,0090	0,2136	16	141,72	24,5	54,02	427,0	16,81
1 1/2	1,10	960	1152	6	IEC100	184C	2,86	74	76	10,95	9,12	96,97	80,80	0,0090	0,2136	16	141,72	24,5	54,02	427,0	16,81
1 1/2	1,10	730	876	8	IEC100	182C	2,99	71	73	14,40	12,00	127,52	106,26	0,0100	0,2373	16	141,72	27,0	59,54	427,0	16,81
1 1/2	1,10	730	876	8	IEC100	184C	2,99	71	73	14,40	12,00	127,52	106,26	0,0100	0,2373	16	141,72	27,0	59,54	427,0	16,81
2	1,50	2830	3396	2	IEC80	56C	3,71	78	80	5,06	4,22	44,85	37,38	0,0012	0,0285	10	88,57	12,8	28,22	317,0	12,48
2	1,50	2830	3396	2	IEC80	143C	3,71	78	80	5,06	4,22	44,85	37,38	0,0012	0,0285	10	88,57	12,8	28,22	318,5	12,54
2	1,50	2830	3396	2	IEC80	145C	3,71	78	80	5,06	4,22	44,85	37,38	0,0012	0,0285	10	88,57	12,8	28,22	318,5	12,54
2	1,50	2860	3432	2	IEC100	182C	3,71	78	80	5,01	4,18	44,38	36,99	0,0053	0,1258	10	88,57	20,8	45,87	407,0	16,02
2	1,50	2860	3432	2	IEC100	184C	3,71	78	80	5,01	4,18	44,38	36,99	0,0053	0,1258	10	88,57	20,8	45,87	407,0	16,02
2	1,50	1440	1728	4	IEC100	182C	3,71	78	80	9,95	8,29	88,15	73,46	0,0075	0,1780	16	141,72	24,0	52,92	427,0	16,81
2	1,50	1440	1728	4	IEC100	184C	3,71	78	80	9,95	8,29	88,15	73,46	0,0075	0,1780	16	141,72	24,0	52,92	427,0	16,81
2	1,50	940	1128	6	IEC100	182C	3,85	75	77	15,25	12,70	135,04	112,53	0,0090	0,2136	16	141,72	24,5	54,02	427,0	16,81
2	1,50	940	1128	6	IEC100	184C	3,85	75	77	15,25	12,70	135,04	112,53	0,0090	0,2136	16	141,72	24,5	54,02	427,0	16,81
2	1,50	680	816	8	IEC100	182C	4,07	71	73	21,08	17,56	186,67	155,56	0,0120	0,2848	32	283,44	30,5	67,25	440,0	17,32
2	1,50	680	816	8	IEC100	184C	4,07	71	73	21,08	17,56	186,67	155,56	0,0120	0,2848	32	283,44	30,5	67,25	440,0	17,32
3	2,20	2860	3432	2	IEC100	182C	5,37	79	81	7,35	6,12	65,10	54,25	0,0053	0,1258	16	141,72	23,5	51,82	427,0	16,81
3	2,20	2860	3432	2	IEC100	184C	5,37	79	81	7,35	6,12	65,10	54,25	0,0053	0,1258	16	141,72	23,5	51,82	427,0	16,81
3	2,20	2860	3432	2	IEC100	213C	5,37	79	81	7,35	6,12	65,10	54,25	0,0053	0,1258	16	141,72	23,5	51,82	429,0	16,89
3	2,20	2860	3432	2	IEC100	215C	5,37	79	81	7,35	6,12	65,10	54,25	0,0053	0,1258	16	141,72	23,5	51,82	429,0	16,89
3	2,20	1410	1692	4	IEC100	182C	5,43	78	80	14,91	12,42	132,04	110,03	0,0075	0,1780	16	141,72	24,0	52,92	427,0	16,81
3	2,20	1410	1692	4	IEC100	184C	5,43	78	80	14,91	12,42	132,04	110,03	0,0075	0,1780	16	141,72	24,0	52,92	427,0	16,81
3	2,20	1410	1692	4	IEC100	213C	5,43	78	80	14,91	12,42	132,04	110,03	0,0075	0,1780	16	141,72	24,0	52,92	429,0	16,89
3	2,20	1410	1692	4	IEC100	215C	5,43	78	80	14,91	12,42	132,04	110,03	0,0075	0,1780	16	141,72	24,0	52,92	429,0	16,89
3	2,20	940	1128	6	IEC100	182C	5,43	78	80	22,36	18,63	198,06	165,05	0,0110	0,2610	32	283,44	29,5	65,05	440,0	17,32
3	2,20	940	1128	6	IEC100	184C	5,43	78	80	22,36	18,63	198,06	165,05	0,0110	0,2610	32	283,44	29,5	65,05	440,0	17,32
3	2,20	940	1128	6	IEC100	213C	5,43	78	80	22,36	18,63	198,06	165,05	0,0110	0,2610	32	283,44	29,5	65,05	442,0	17,40
3	2,20	940	1128	6	IEC100	215C	5,43	78	80	22,36	18,63	198,06	165,05	0,0110	0,2610	32	283,44	29,5	65,05	442,0	17,40
4	3,00	2860	3432	2	IEC100	182C	7,14	81	83	10,02	8,35	88,77	73,97	0,0053	0,1258	16	141,72	26,0	57,33	427,0	16,81
4	3,00	2860	3432	2	IEC100	184C	7,14	81	83	10,02	8,35	88,77	73,97	0,0053	0,1258	16	141,72	26,0	57,33	427,0	16,81
4	3,00	2860	3432	2	IEC100	213C	7,14	81	83	10,02	8,35	88,77	73,97	0,0053	0,1258	16	141,72	26,0	57,33	429,0	16,89
4	3,00	2860	3432	2	IEC100	215C	7,14	81	83	10,02	8,35	88,77	73,97	0,0053	0,1258	16	141,72	26,0	57,33	429,0	16,89
4	3,00	1410	1692	4	IEC100	182C	7,41	78	80	20,33	16,94	180,05	150,04	0,0085	0,2017	32	283,44	29,5	65,05	440,0	17,32
4	3,00	1410	1692	4	IEC100	184C	7,41	78	80	20,33	16,94	180,05	150,04	0,0085	0,2017	32	283,44	29,5	65,05	440,0	17,32
4	3,00	1410	1692	4	IEC100	213C	7,41	78	80	20,33	16,94	180,05	150,04	0,0085	0,2017	32	283,44	29,5	65,05	442,0	17,40
4	3,00	1410	1692	4	IEC100	215C	7,41	78	80	20,33	16,94	180,05	150,04	0,0085	0,2017	32	283,44	29,5	65,05	442,0	17,40
5 1/2	4,00	2860	3432	2	IEC100	182C	9,18	84	87	13,36	11,14	118,36	98,63	0,0085	0,2017	16	141,72	26,0	57,33	427,0	16,81
5 1/2	4,00	2860	3432	2	IEC100	184C	9,18	84	87	13,36	11,14	118,36	98,63	0,0085	0,2017	16	141,72	26,0	57,33	427,0	16,81
5 1/2	4,00	2860	3432	2	IEC100	213C	9,18	84	87	13,36	11,14	118,36	98,63	0,0085	0,2017	16	141,72	26,0	57,33	429,0	16,89
5 1/2	4,00	2860	3432	2	IEC100	215C	9,18	84	87	13,36	11,14	118,36	98,63	0,0085	0,2017	16	141,72	26,0	57,33	429,0	16,89
5 1/2	4,00	1410	1692	4	IEC100	182C	9,88	78	80	27,10	22,59	240,07	200,06	0,0110	0,2610	32	283,44	29,5	65,05	440,0	17,32
5 1/2	4,00	1410	1692	4	IEC100	184C	9,88	78	80	27,10	22,59	240,07	200,06	0,0110	0,2610	32	283,44	29,5	65,05	440,0	17,32
5 1/2	4,00	1410	1692	4	IEC100	213C	9,88	78	80	27,10	22,59	240,07	200,06	0,0110	0,2610	32	283,44	29,5	65,05	442,0	17,40
5 1/2	4,00	1410	1692	4	IEC100	215C	9,88	78	80	27,10	22,59	240,07	200,06	0,0110	0,2610	32	283,44	29,5	65,05	442,0	17,40