



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

2 POLI 3000 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∅	Watt	Kg	Nm	∅	VA	Kg	Nm	∅	Watt	Kg	Nm	∅	Watt	Kg
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AT56A	1	9700	12	4,0	-	-	-	-	-	-	-	-	-	-	-	-
AT56B	1	8900	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63A	4	8100	20	5,0	5	8100	40	5,0	3	8100	18	5,0	7,5	8100	11,5	4,3
AT63B	4	6750	20	6,0	5	6750	40	6,0	3	6750	18	6,0	7,5	6750	11,5	4,9
AT63C	4	5400	20	7,0	5	5400	40	7,0	3	5400	18	7,0	7,5	5400	11,5	6,2
AT71A	4	5400	20	8,0	5	5400	40	8,0	4	5400	18	7,0	7,5	5400	11,5	6,4
AT71B	4	5400	20	8,0	5	5400	40	8,0	4	5400	18	8,0	7,5	5400	11,5	6,8
AT71C	4	5500	20	9,0	5	5500	40	9,0	4	5500	18	9,0	7,5	5500	11,5	8,0
AT80A	8	5400	25	11,0	10	5400	70	11,0	9	5400	25	11,0	15,0	5400	16,0	9,6
AT80B	8	5400	25	12,0	10	5400	70	12,0	9	5400	25	12,0	15,0	5400	16,0	10,9
AT80C	8	5100	25	13,0	10	5100	70	13,0	9	5100	25	13,0	15,0	5100	16,0	11,6
AT80D	8	4900	25	14,0	10	4900	70	14,0	9	4900	25	14,0	15,0	4900	16,0	12,6
AT90S	16	4000	30	17,0	20	4000	120	17,0	10	4000	25	14,0	30,0	4000	16,0	14,0
AT90L	16	4000	30	18,0	20	4000	120	18,0	10	4000	25	15,0	30,0	4000	16,0	15,5
AT90LB	16	3800	30	20,0	20	3800	120	20,0	10	3800	25	18,0	30,0	3800	16,0	17,5
AT100A	32	2500	40	25,0	40	2500	160	27,0	12	2500	35	22,0	60,0	2500	21,0	22,0
AT100B	32	2400	40	28,0	40	2400	160	30,0	12	2400	35	25,0	60,0	2400	21,0	24,5
AT112A	60	1500	50	36,0	60	1500	300	36,0	13	1500	35	31,0	120,0	1500	21,0	33,0
AT112B	60	1400	50	41,0	60	1400	300	41,0	13	1400	35	36,0	120,0	1400	21,0	38,0
AT112BL	60	1300	50	43,0	60	1300	300	43,0	13	1300	35	38,0	120,0	1300	21,0	40,0
AT132S	80	430	55	58,0	90	430	500	59,0	17	430	35	50,0	240,0	430	28,0	57,0
AT132SL	80	430	55	61,0	90	430	500	62,0	17	430	35	58,0	240,0	430	28,0	60,0
AT132M	80	400	55	67,0	90	400	500	68,0	17	400	35	59,0	240,0	400	28,0	66,0
AT132ML	80	400	55	71,0	90	400	500	72,0	17	400	35	63,0	240,0	400	28,0	70,0
AT160MA	150	300	85	95,0	200	300	600	93,0	30	300	65	82,0	480,0	300	38,0	96,0
AT160MB	150	300	85	108,0	200	300	600	106,0	30	300	65	95,0	480,0	300	38,0	109,0
AT160L	150	300	85	111,0	200	300	600	117,0	30	300	65	106,0	480,0	300	38,0	120,0
AT180M	260	200	100	119,0	400	200	600	130,0	-	-	-	-	480,0	200	38,0	131,0
AT200LA	400	100	100	149,0	400	100	600	150,0	-	-	-	-	480,0	100	38,0	151,0
AT200LB	400	100	100	169,0	400	100	600	170,0	-	-	-	-	480,0	100	38,0	171,0



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

4 POLI 1500 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∞∞	Watt	Kg	Nm	∞∞	VA	Kg	Nm	∞∞	Watt	Kg	Nm	∞∞	Watt	Kg
AT50A	1	12500	12	3,7	-	-	-	-	-	-	-	-	-	-	-	-
AT50B	1	12500	12	3,9	-	-	-	-	-	-	-	-	-	-	-	-
AT56A	1	12500	12	4,0	-	-	-	-	-	-	-	-	-	-	-	-
AT56B	1	12500	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT56C	1	12500	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63A	4	10500	20	5,0	5	10500	40	5,0	3	10500	17	5,0	7,5	10500	11,5	4,3
AT63B	4	10500	20	7,0	5	10500	40	7,0	3	10500	17	6,0	7,5	10500	11,5	4,9
AT63C	4	10500	20	7,0	5	10500	40	7,0	3	10500	17	6,0	7,5	10500	11,5	4,9
AT63D	4	10500	20	8,0	5	10500	40	8,0	3	10500	17	7,0	7,5	10500	11,5	5,9
AT71A	4	18000	20	8,0	5	18000	40	8,0	4	18000	17	7,0	7,5	18000	11,5	6,4
AT71B	4	17000	20	8,0	5	17000	40	8,0	4	17000	17	8,0	7,5	17000	11,5	6,8
AT71C	4	16000	20	9,0	5	16000	40	9,0	4	16000	17	9,0	7,5	16000	11,5	8,0
AT80A	8	9000	25	11,0	10	9000	70	11,0	9	9000	34	11,0	15,0	9000	16,0	9,6
AT80B	8	9000	25	13,0	10	9000	70	13,0	9	9000	34	12,0	15,0	9000	16,0	10,9
AT80C	8	9000	25	13,5	10	9000	70	13,5	9	9000	34	13,5	15,0	9000	16,0	11,6
AT80D	8	9000	25	14,0	10	9000	70	14,0	9	9000	34	14,0	15,0	9000	16,0	12,1
AT90S	16	13500	30	17,0	20	13500	120	17,0	10	13500	34	15,0	30,0	13500	16,0	14,0
AT90L	16	11000	30	18,0	20	11000	120	18,0	10	11000	34	16,0	30,0	11000	16,0	15,5
AT90LB	16	8000	30	20,0	20	8000	120	20,0	10	8000	34	18,0	30,0	8000	16,0	17,5
AT100A	32	7200	40	25,5	40	7200	160	27,5	12	7200	40	22,5	60,0	7200	21,0	22,5
AT100B	32	6300	40	28,0	40	6300	160	30,0	12	6300	40	25,0	60,0	6300	21,0	24,5
AT100BL	32	6000	40	30,0	40	6000	160	32,0	12	6000	40	27,0	60,0	6000	21,0	26,5
AT112A	60	3600	50	38,0	60	3600	300	38,0	13	3600	40	33,0	120,0	3600	21,0	35,0
AT112BL	60	3400	50	44,0	60	3400	300	44,0	13	3400	40	39,0	120,0	3400	21,0	41,0
AT132S	80	1100	55	56,0	90	1100	500	57,0	17	1100	40	48,0	240,0	1100	28,0	55,0
AT132M	80	850	55	66,0	90	850	500	67,0	17	850	40	57,0	240,0	850	28,0	64,0
AT132ML	80	800	55	68,0	90	800	500	69,0	17	800	40	59,0	240,0	800	28,0	66,0
AT160M	150	750	85	87,0	200	750	600	85,0	30	750	45	75,0	480,0	750	38,0	111,0
AT160L	150	750	85	97,0	200	750	600	95,0	30	750	45	83,0	480,0	750	38,0	121,0
AT180M	260	200	100	129,0	400	200	600	140,0	-	-	-	-	480,0	200	38,0	141,0
AT180L	260	200	100	154,0	400	200	600	155,0	-	-	-	-	480,0	200	38,0	156,0
AT200L	400	100	100	174,0	400	100	600	175,0	-	-	-	-	480,0	100	38,0	176,0



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

6 POLI 1000 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∅	Watt	Kg	Nm	∅	VA	Kg	Nm	∅	Watt	Kg	Nm	∅	Watt	Kg
AT56B	1	21500	12	4,0	-	-	-	-	-	-	-	-	-	-	-	-
AT56C	1	21500	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63B	4	18000	20	5,0	5	18000	40	5,0	3	18000	17	5,0	7,5	18000	11,5	4,4
AT63C	4	18000	20	6,0	5	18000	40	6,0	3	18000	17	6,0	7,5	18000	11,5	4,6
AT71A	4	25000	20	7,0	5	25000	40	7,0	4	25000	17	7,0	7,5	25000	11,5	6,3
AT71B	4	25000	20	8,0	5	25000	40	8,0	4	25000	17	8,0	7,5	25000	11,5	6,6
AT71C	4	24000	20	8,0	5	24000	40	8,0	4	24000	17	8,0	7,5	24000	11,5	7,1
AT80A	8	16000	25	11,0	10	16000	70	11,0	9	16000	34	11,0	15,0	16000	16,0	9,8
AT80B	8	16000	25	13,0	10	16000	70	13,0	9	16000	34	13,0	15,0	16000	16,0	11,6
AT80C	8	15000	25	14,0	10	15000	70	14,0	9	15000	34	14,0	15,0	15000	16,0	12,1
AT90S	16	15000	30	17,0	20	15000	120	17,0	10	15000	34	15,0	30,0	15000	16,0	14,0
AT90L	16	13500	30	18,0	20	13500	120	18,0	10	13500	34	17,0	30,0	13500	16,0	16,0
AT90LB	16	13000	30	19,5	20	13000	120	19,5	10	13000	34	18,5	30,0	13000	16,0	18,0
AT100A	32	10000	40	26,0	40	10000	160	28,0	12	10000	40	23,0	60,0	10000	21,0	23,0
AT100B	32	7500	40	28,0	40	7500	160	30,0	12	7500	40	25,0	60,0	7500	21,0	24,5
AT100BL	32	7000	40	30,0	40	7000	160	32,0	12	7000	40	27,0	60,0	7000	21,0	26,5
AT112A	60	6000	50	39,0	60	6000	300	39,0	13	6000	40	40,0	120,0	6000	21,0	36,0
AT112B	60	5500	50	46,0	60	5500	300	46,0	13	5500	40	41,0	120,0	5500	21,0	43,0
AT132S	80	1600	55	56,0	90	1600	500	57,0	17	1600	40	48,0	240,0	1600	28,0	55,0
AT132M	80	1350	55	65,0	90	1350	500	66,0	17	1350	40	57,0	240,0	1350	28,0	64,0
AT132ML	80	1100	55	68,0	90	1100	500	69,0	17	1100	40	60,0	240,0	1100	28,0	67,0
AT160M	150	1000	85	89,0	200	1000	600	85,0	30	1000	65	77,0	480,0	1000	38,0	91,0
AT160L	150	850	85	102,0	200	850	600	105,0	30	850	65	97,0	480,0	850	38,0	111,0
AT180L	260	200	100	144,0	400	200	600	144,0	-	-	-	-	480,0	650	38,0	146,0
AT200LA	400	100	100	159,0	400	100	600	159,0	-	-	-	-	480,0	450	38,0	161,0
AT200LB	400	100	100	179,0	400	100	600	179,0	-	-	-	-	480,0	450	38,0	181,0



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

8 POLI 750 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∅	Watt	Kg	Nm	∅	VA	Kg	Nm	∅	Watt	Kg	Nm	∅	Watt	Kg
AT56B	1	27000	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63B	4	22500	20	6,0	5	22500	40	6,0	3	22500	17	5,0	7,5	22500	11,5	4,5
AT63C	4	22500	20	6,0	5	22500	40	6,0	3	22500	17	6,0	7,5	22500	11,5	4,9
AT71B	4	27000	20	7,0	5	27000	40	7,0	4	27000	17	7,0	7,5	27000	11,5	6,3
AT71C	4	27000	20	8,0	5	27000	40	8,0	4	27000	17	8,0	7,5	27000	11,5	7,0
AT80A	8	27000	25	11,0	10	27000	70	11,0	9	27000	34	10,0	15,0	27000	16,0	9,9
AT80B	8	27000	25	13,0	10	27000	70	13,0	9	27000	34	13,0	15,0	27000	16,0	11,6
AT80C	8	25500	25	14,0	10	25500	70	14,0	9	25500	34	14,0	15,0	25500	16,0	12,1
AT90S	16	18000	30	17,0	20	18000	120	17,0	10	18000	34	15,0	30,0	18000	16,0	14,0
AT90L	16	15000	30	18,0	20	15000	120	18,0	10	15000	34	17,0	30,0	15000	16,0	16,0
AT90LB	16	14500	30	20,0	20	14500	120	20,0	10	14500	34	19,0	30,0	14500	16,0	18,0
AT100A	32	12500	40	26,0	40	12500	160	28,0	12	12500	40	24,0	60,0	12500	21,0	23,3
AT100B	32	8500	40	29,0	40	8500	160	31,0	12	8500	40	26,0	60,0	8500	21,0	25,5
AT100BL	32	8000	40	31,0	40	8000	160	33,0	12	8000	40	28,0	60,0	8000	21,0	27,5
AT112A	60	6500	50	41,0	60	6500	300	41,0	13	6500	40	36,0	120,0	6500	21,0	38,0
AT132S	80	1900	55	57,0	90	1900	500	58,0	17	1900	40	49,0	240,0	1900	28,0	56,0
AT132M	80	1900	55	66,0	90	1900	500	67,0	17	1900	40	58,0	240,0	1900	28,0	65,0
AT132ML	80	1900	55	71,0	90	1900	500	72,0	17	1900	40	63,0	240,0	1900	28,0	70,0
AT160MA	150	1600	85	83,0	200	1600	600	81,0	30	1600	65	71,0	480,0	1600	38,0	85,0
AT160MB	150	1600	85	91,0	200	1600	600	89,0	30	1600	65	79,0	480,0	1600	38,0	93,0
AT160L	150	1600	85	105,0	200	1600	600	103,0	30	1600	65	93,0	480,0	1600	38,0	107,0
AT180L	260	200	100	119,0	400	200	600	139,0	-	-	-	-	480,0	1300	38,0	141,0
AT200LA	400	100	100	149,0	400	100	600	164,0	-	-	-	-	480,0	900	38,0	166,0



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

12 POLI 500 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	ωO	Watt	Kg	Nm	ωO	VA	Kg	Nm	ωO	Watt	Kg	Nm	ωO	Watt	Kg
AT71C	4	21500	20	8,0	5	21500	40	8,0	4	21500	17	8,0	7,5	21500	11,5	7,1
AT80C	8	21500	25	14,0	10	21500	70	14,0	9	21500	34	14,0	15,0	21500	16,0	12,1
AT90L	16	27000	30	19,0	20	27000	120	19,0	10	27000	34	18,0	30,0	27000	16,0	17,0
AT100B	32	13500	40	25,0	40	13500	160	29,0	12	13500	40	25,0	60,0	13500	21,0	24,5
AT100BL	32	11500	40	27,0	40	11500	160	32,0	12	11500	40	27,0	60,0	11500	21,0	26,5
AT112B	60	11000	50	35,0	60	11000	300	37,0	13	11000	40	33,0	120,0	11000	21,0	34,0
AT132S	80	2000	55	66,0	90	2000	500	69,0	17	2000	40	64,0	240,0	2000	28,0	67,0
AT132M	80	2000	55	79,0	90	2000	500	83,0	17	2000	40	75,0	240,0	2000	28,0	78,0
AT132ML	80	1900	55	71,0	90	1900	500	72,0	17	1900	40	63,0	240,0	1900	28,0	78,0
AT160M	150	1650	85	99,0	200	1650	600	95,0	30	1650	65	87,0	480,0	1650	38,0	101,0
AT160L	150	1650	85	109,0	200	1650	600	105,0	30	1650	65	97,0	480,0	1650	38,0	111,0
AT180L	260	200	100	119,0	400	200	600	139,0	-	-	-	-	480,0	1400	38,0	141,0
AT200LA	400	100	100	149,0	400	100	600	169,0	-	-	-	-	480,0	1100	38,0	171,0



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

16 POLI

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∞∞	Watt	Kg	Nm	∞∞	VA	Kg	Nm	∞∞	Watt	Kg	Nm	∞∞	Watt	Kg
AT132S	80	2000	55	66,0	90	2000	500	69,0	17	2000	40	64,0	240,0	2000	28,0	67,0
AT132M	80	2000	55	79,0	90	2000	500	83,0	17	2000	40	75,0	240,0	2000	28,0	78,0
AT160M	150	1650	85	99,0	200	1650	600	95,0	30	1650	65	87,0	480,0	1650	38,0	101,0
AT160L	150	1650	85	109,0	200	1650	600	105,0	30	1650	65	97,0	480,0	1650	38,0	111,0
AT180L	260	200	100	119,0	400	200	600	139,0	-	-	-	-	480,0	1400	38,0	141,0
AT200L	400	100	100	149,0	400	100	600	169,0	-	-	-	-	480,0	1100	38,0	171,0



Motori asincroni trifase autofrenanti serie AT
AT series three-phase induction brake motors
Moteurs asynchrones triphasés autofreinants série AT
Asynchrone Drehstrombremsmotoren Serie AT

32 POLI

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	ωO	Watt	Kg	Nm	ωO	VA	Kg	Nm	ωO	Watt	Kg	Nm	ωO	Watt	Kg
AT180L	260	200	100	119,0	400	200	600	139,0	-	-	-	-	480,0	1400	38,0	141,0
AT200L	400	100	100	149,0	400	100	600	169,0	-	-	-	-	480,0	1100	38,0	171,0