

VENTILATORI VISOKOG PRITISKA

MODEL	Motor Tip	R.P.M.max	I max			m³/h	dB(A)	Ps (max)	
			230	400	690			(Pa)	(mmH2O)
SVVP II. 11 1,1/2	MS 802-2	2770	4,35	2,51	-	1044	78	2300	230
SVVP II. 21 1,5/2	MS 803-2	2800	5,87	3,32	-	1296	79	3200	320
SVVP II. 22 1,5/2	MS 90S-2	2840	5,76	3,28	-	1296	79	3200	320
SVVP II. 31 2,2/2	MS 90L1-2	2840	8	4,61	-	1836	80	3800	380
SVVP II. 41 3/2	MS 90L2-2	2840	10,56	6,1	-	2124	81	4100	410
SVVP II. 42 3/2	MS 100L1-2	2840	10,44	6,03	-	2124	81	4100	410
SVVP II. 41 4/2	MS 100L2-2	2850	-	7,88	4,55	3024	81	4100	410
SVVP II. 42 4/2	MS 112M-2	2880	-	7,88	4,55	3024	81	4100	410
SVVP II. 43 4/2	MS 100L-2	2880	-	7,88	4,55	2376	82	4100	410
SVVP II. 44 4/2	MS 112M-2	2880	-	7,88	4,55	2376	82	4800	480
SVVP II. 41 5,5/2	MS 112L-2	2880	-	10,53	6,08	3384	86	4800	480
SVVP II. 42 5,5/2	MS 132S1-2	2900	-	10,53	6,08	3384	86	4800	480
SVVP II. 51 5,5/2	MS 112L-2	2880	-	10,53	6,08	3384	86	5200	520
SVVP II. 52 5,5/2	MS 132S1-2	2900	-	10,53	6,08	3384	87	5200	520
SVVP II. 51 7,5/2	MS 132S2-2	2920	-	14,14	8,16	4680	87	5200	520
SVVP II. 51 7,5/2	MS 132S2-2	2920	-	14,14	8,16	3600	87	6000	600
SVVP II. 61 11/2	MS 132M2-2	2930	-	19,96	11,52	6084	89	6600	660
SVVP II. 62 11/2	MS 160M1-2	2940	-	19,96	11,52	6084	89	6600	660
SVVP II. 63 11/2	MS 132M2-2	2930	-	19,96	11,52	4140	89	7500	750
SVVP II. 64 11/2	MS 160M1-2	2940	-	19,96	11,52	4140	89	7500	750
SVVP II. 61 15/2	Y2 160M-2	2930	-	27,3	15,36	6804	89	7500	750
SVVP II. 71 18,5/2	Y2 160M-2	2930	-	33	18,82	6804	91	8500	850
SVVP II. 71 22/2	Y2 180M-2	2940	-	39,2	23	9504	93	8500	850
SVVP II. 72 22/2	Y2 180M-2	2940	-	39,2	23	6804	93	10000	1000
SVVP II. 71 30/2	Y2 180M-2	2950	-	52,8	32,3	10800	94	10000	1000
SVVP II. 81 30/2	Y2 180M-2	2950	-	52,8	32,3	8460	95	11000	1100
SVVP II. 81 37/2	Y2 200L2-2	2950	-	64,5	39,5	11880	95	11000	1100
SVVP II. 82 37/2	Y2 200L2-2	2950	-	64,5	39,5	8460	96	12500	1250
SVVP II. 81 45/2	Y2 200L2-2	2970	-	78,2	45	13428	96	12500	1250
SVVP II. 91 55/2	Y2 250M-2	2970	-	95,4	56,5	11800	96	14000	1400
SVVP II. 91 75/2	Y2 250M-2	2970	-	129,3	76,3	21600	97	14000	1400

VENTILATORI VISOKOG PRITISKA

MODEL	Motor Tip	R.P.M.max	I max			m ³ /h	dB(A)	Ps (max)	
			230	400	690			(Pa)	(mmH ₂ O)
SVVP II. 92 75/2	Y2 250M-2	2970	-	129,3	76,3	15228	97	16000	1600
SVVP II. 91 90/2	Y2 280M-2	2970	-	152,2	76,3	23760	97	16000	1600
SVVP II. 101 90/2	Y2 280M-2	2970	-	152,2	76,3	15228	98	17800	1780
SVVP II. 101 110/2	Y2 280M-2	2970	-	185,6	86,7	23760	98	17800	1780
SVVP II. 102 110/2	Y2 280M-2	2970	-	185,6	86,7	17028	99	19500	1950
SVVP II. 101 132/2	Y2 315M-2	2980	-	221,6	131,2	26640	99	19500	1950